

DURACELL®

BATTERY CHARGERS

Portable Power



Portable Charging

Retail Package



www.duracellpower.com

Simple Plug-n-Charge Solutions

The Duracell® line of Battery Chargers feature rapid charge technology for faster, more accurate charging, and do not require installation or set up. The simple plug-and-charge solution makes these chargers ideal for extending and recharging all types of 12-volt lead acid batteries. The three stage charging process ensures the battery is always fully charged, but never overcharged. Most units are conveniently packaged in a hard plastic carrying case that makes these chargers portable and easy to use.

Product Features:

- ▶ Three stage charging extends battery life
- ▶ Rapid charge technology for faster, more accurate charging
- ▶ Selectable charge rate for all types of 12-volt lead-acid batteries
- ▶ Short-circuit protection for safe operation
- ▶ Easy battery connection through clip leads connected to the unit
- ▶ Plug-and-play charging solution; requires no installation or setup
- ▶ Small footprint, lightweight and easy to use
- ▶ Convenient carry case holds battery charger and cables

Product Applications:

Recharge and maintain:

- ▶ Motorcycle
- ▶ ATV
- ▶ Snowmobile
- ▶ Personal watercraft
- ▶ Lawn tractor
- ▶ Compact car
- ▶ Minivan
- ▶ SUV
- ▶ RV
- ▶ Truck batteries (deep cycle)

Product Specifications

Models	6 AMP
Output current	2/4/6 A
Output voltage (nominal)	12 Vdc
Float voltage	13.5 Vdc
AC input voltage	120 Vac 60 Hz
Recommended battery type	12 V (AGM, Gel, Flooded lead-acid)
Recommended battery size	6 - 60 Ah
Charging type*	Three stage
Charging efficiency	70%

General Specifications

Part number	804-0006-10
Unit dimensions (L x W x H)	6.3 x 3.9 x 2.2" (16.0 x 10.0 x 5.5 cm)
Unit weight	1.54 lb (0.70 kg)
Warranty	Twelve months
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	77°F to 158°F (-25°C to 70°C)
Regulatory approvals	ETL approved to CSA 107.2, UL 1236, FCC Class B

Packaging Specification

Retail Packaging	
Packaging Type	Hard Plastic Case
Size (L x W x H)	13.5 x 8.0 x 3.5" (34.3 x 20.3 x 91.0 cm)
Count	1
Weight	3.0 lb (1.36 kg)
Inner Carton	
Size (L x W x H)	18.0 x 14.0 x 8.5 (45.7 x 35.6 x 21.6)
Count	5
Weight	16.58 lb (7.5 kg)
Master Carton	
Size (L x W x H)	19.0 x 15.0 x 18.0" (48.3 x 38.1 x 45.8 cm)
Count	10
Weight	35.1 lb (15.9 kg)
UPC number	609525752434

Specifications subject to change without notice.

*Three-Stage Charging

Multistage charging ensures batteries receive optimum charging, but with minimal wear and tear, regulating the voltage and current delivered to the batteries in three automatic stages;

Bulk: Replaces 70-80% of the battery's state of charge at the fastest possible rate.

Absorption: Replenishes the remaining 20-30% of charge, bringing the battery to a full charge at a slow, safe rate.

Float: Voltage is reduced and held constant in order to prevent damage and keep batteries at a full charge.

