

DURACELL®

BATTERY CHARGERS

Portable Power



Portable Charging

Simple Plug-n-Charge Solutions

The Duracell® line of Battery Chargers feature rapid charge technology for faster, more accurate charging, and do not require installation or set up. The simple plug-and-charge solution makes these chargers ideal for extending and recharging all types of 12-volt lead acid batteries. The three stage charging process ensures the battery is always fully charged, but never overcharged. Most units are conveniently packaged in a hard plastic carrying case that makes these chargers portable and easy to use.

Product Features:

- ▶ Three stage charging extends battery life
- ▶ Rapid charge technology for faster, more accurate charging
- ▶ Selectable charge rate for all types of 12-volt lead-acid batteries
- ▶ Short-circuit protection for safe operation
- ▶ Easy battery connection through clip leads connected to the unit
- ▶ Plug-and-play charging solution; requires no installation or setup
- ▶ Small footprint, lightweight and easy to use
- ▶ Convenient carry case holds battery charger and cables

Product Applications:

Recharge and maintain:

- ▶ Motorcycle
- ▶ ATV
- ▶ Snowmobile
- ▶ Personal watercraft
- ▶ Lawn tractor
- ▶ Compact car
- ▶ Minivan
- ▶ SUV
- ▶ RV
- ▶ Truck batteries (deep cycle)

Retail Package



www.duracellpower.com

Product Specifications

Models	6 AMP	12 AMP	25 AMP
Output current	2/4/6 A	2/6/12 A	2/6/12/ 25 A
Output voltage (nominal)	12 Vdc	12 Vdc	14.4 Vdc
Float voltage	13.5 Vdc	13.5 Vdc	13.5 Vdc
AC input voltage	120 Vac 60 Hz	120 Vac 60 Hz	120 Vac 60 Hz
Recommended battery type	12 V (AGM, Gel, Flooded lead-acid)	12 V (AGM, Gel, Flooded lead-acid)	12 V (AGM, Gel, Flooded lead-acid)
Recommended battery size	6 - 60 Ah	6 - 120 Ah	6 - 400 Ah
Charging type*	Three stage	Three stage	Three stage
Charging efficiency	70%	70%	70%

General Specifications

Part number	804-0006-10	804-0012-10	804-0025-10
Unit dimensions (L x W x H)	6.3 x 3.9 x 2.2" (16.0 x 10.0 x 5.5 cm)	8.3 x 3.9 x 2.2" (21.0 x 10.0 x 5.5 cm)	9.1 x 5.1 x 3.1" (23.2 x 13.0 x 7.8 cm)
Unit weight	1.5 lb (0.70 kg)	2.1 lb (0.95 kg)	3.9 lb (1.78 kg)
Warranty	Twelve months	Twelve months	Twelve months
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Storage temperature	77°F to 158°F (-25°C to 70°C)	77°F to 158°F (-25°C to 70°C)	77°F to 158°F (-25°C to 70°C)
Regulatory approvals	ETL approved to CSA 107.2, UL 1236, FCC Class B	ETL approved to CSA 107.2, UL 1236, FCC Class B	ETL approved to CSA 107.2, UL 1236, FCC Class B

Packaging Specification

Retail Packaging

Packaging Type	Hard Plastic Case	Hard Plastic Case	Hard Plastic Case
Size (L x W x H)	14.0 x 8.0 x 3.6" (35.6 x 20.3 x 91.0 cm)	14.0 x 8.0 x 3.6" (35.6 x 20.3 x 91.0 cm)	15.4 x 8.9 x 4.1" (39.0 x 22.5 x 10.5 cm)
Count	1	1	1
Weight	3.0 lb (1.36 kg)	3.6 lb (1.63 kg)	5.9 lb (2.67 kg)

Inner Carton

Size (L x W x H)	N/A	N/A	N/A
Count	N/A	N/A	N/A
Weight	N/A	N/A	N/A

Master Carton

Size (L x W x H)	15.0 x 14.4 x 9.0" (38 x 36.5 x 23 cm)	15.0 x 14.4 x 9.0" (38 x 36.5 x 23 cm)	16.0 x 8.9 x 9.5" (40.5 x 22.5 x 24 cm)
Count	4	4	2
Weight	13.3 lb (6.1 kg)	15.5 lb (7.1 kg)	12.8 lb (5.8 kg)
UPC number	609525752434	609525752441	609525752458

Specifications subject to change without notice.


*Three-Stage Charging

Multistage charging ensures batteries receive optimum charging, but with minimal wear and tear, regulating the voltage and current delivered to the batteries in three automatic stages;

Bulk: Replaces 70-80% of the battery's state of charge at the fastest possible rate.

Absorption: Replenishes the remaining 20-30% of charge, bringing the battery to a full charge at a slow, safe rate.

Float: Voltage is reduced and held constant in order to prevent damage and keep batteries at a full charge.



Battery-Biz Inc.

1380 Flynn Road
Camarillo, CA 93012
www.battery-biz.com

Ph. 800.848.6782
Fax 805.437.7722
International 805.437.7777