

# DURACELL®

## POWERPACK 300

Portable & Emergency  
Power



### Provides Portable Emergency Power

The Duracell® Powerpack 300 is easy to use and ready when you need it most. It gives you the power to jump-start your vehicle or inflate tires during roadside emergencies. Its detachable ultra bright LED flashlight makes a power outage easier to deal with. Combine this with 300 watts of portable AC power to operate small appliance or recharge electronics, and you have the power to be prepared anytime, anywhere.

### Product Features:

- ▶ 300 watts of household power
- ▶ 250 psi air compressor
- ▶ 200 amps to jumpstart your vehicle
- ▶ Detachable ultra bright LED flashlight
- ▶ Reverse-polarity detector to safely jump-start your vehicle
- ▶ Jump-start clips designed for easy storage on the unit
- ▶ Overload and over-temperature protection to ensure longer inverter life

### Product Applications:

- ▶ Charges cordless & cellular phones
- ▶ Powers two-way radio sets
- ▶ Jump-starts your car (200 CCA)
- ▶ Inflates vehicle tires
- ▶ Powers camcorders, video games, stereos and digital cameras
- ▶ Runs fans, laptops and clock radios



Vehicle jump-starter



Detachable flashlight

### Retail Package



[www.duracellpower.com](http://www.duracellpower.com)

### Product Specifications

#### AC

AC output power (max. continuous)	240 W
AC output power (peak)	300 W
AC output surge capacity (peak)	480 W
AC output voltage (nominal)	120 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Inverter no-load current	< 0.20 amps (battery drain with no load on inverter)
Inverter low-battery alarm	11.0 V
Inverter low-battery shutdown	10.5 V

#### DC

Internal battery type	Sealed lead-acid, AGM
Internal battery capacity	12 Ah, 120 CCA
Internal battery voltage	12 Vdc
DC power socket (circuit breaker)	12 A (automatic reset)

### General Specifications

Part number	852-0307
Unit dimensions (L x W x H)	12.5 x 9.25 x 8" (31.8 x 23.5 x 20.3 cm)
Unit weight	14.3 lb (6.5 kg)
Warranty	Twelve months
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	32°F to 86°F (0°C to 30°C)

Jump-start cables	24" (610 mm), 8 AWG
Air compressor	250 psi
Flashlight	LED (rechargeable)

### Charging System

AC charger bulk charging current	500 mA (maximum)
Peak charging voltage	14.2 V (nominal)
Charge restart voltage	12.9 V (nominal)
Float charge current	1 mA (nominal)
Charger input socket current	3 A (maximum)

### Charging Time

From AC outlet	Max. 24 hours*
From DC outlet	Max. 2.5 hours*


\*Maximum charging time occurs when battery is completely discharged

### Packaging Specifications

	Retail Package*	Master Carton	Pallet
Size (L x W x H)	14.6 x 10.4 x 10" (37 x 26.5 x 25.5 cm)	15 x 10.75 x 10.5" (38.1 x 27.3 x 26.7 cm)	40 x 48 x 77.5" (101.6 x 121.9 x 196.8 cm)
Count	1	1	63
Weight	17 lb (7.7 kg)	19 lb (8.6 kg)	N/A
Volume	N/A	1,693 cu.in.	N/A
UPC number	609525752243		

\* Box

Specifications subject to change without notice



## Battery-Biz Inc.

1380 Flynn Road  
Camarillo, CA 93012  
www.battery-biz.com

Ph. 800.848.6782  
Fax 805.437.7722  
International 805.437.7777