

DURACELL®

POWERSOURCE MOBILE 100

Portable Power



Portable Power for Laptop and Mobile Devices

The Duracell® PowerSource Mobile 100 is a stand-alone power source with a rechargeable battery with both AC and USB outlets. It is ideal for people who frequently travel by vehicle and/or airplane, providing up to two hours of additional runtime for a laptop. If you need more play time with your portable game console or DVD player, simply connect your device into the AC outlet and keep going. Two USB charge ports will keep your BlackBerry®, iPaq®, Palm® or iPod® charged when you need it most. You no longer have to carry extra cords, chargers and device-specific batteries. You'll save money and space in your laptop carry bag!

Product Features:

- ▶ Combines a 100-watt inverter with a lightweight, high-output 4.0 amp-hour lithium-ion battery pack
- ▶ Converts 12-volt DC power from a vehicle battery into 120-volt AC power
- ▶ Three-prong AC outlet to handle all chargers and adapters for mobile electronics
- ▶ Two USB charge ports
- ▶ Blue LED On/Off indicator
- ▶ DC cable with vehicle and airplane connector
- ▶ Lightweight AC charging adapter
- ▶ LED battery status / charge status indicator

Protection Features:

- ▶ Over-temperature shutdown
- ▶ Low-battery voltage shutdown (10.5 volt DC with automatic reset)
- ▶ Overload shutdown
- ▶ Electronic ground fault circuit interrupter (GFCI)



Portable power anywhere



Two hours of extra runtime for a laptop

Retail Package



www.duracellpower.com

Product Specifications

AC

AC output power (continuous)	80 W
AC output power (5 minutes)	100 W
AC output surge capacity (peak)	160 W
AC output voltage	120 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Internal AC charger	2 A

DC

Internal battery type	Li-Ion Polymer
Internal battery capacity	4 Ah
Internal battery voltage	11.1 Vdc
Inverter no-load current	< 200 mA

General Specifications

Part number	852-0281-07
Unit dimensions (L x W x H)	5.375 x 3.125 x 1.5" (13.7 x 7.9 x 3.8 cm)
Unit weight	1.1 lb (0.5 kg)
Warranty	One year
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	32°F to 104°F (0°C to 40°C)

Charging System

AC charger bulk charging current	1 A (maximum)
Peak charging voltage	12.6 V (nominal)

Charging Times

Battery discharge levels	1	0.75	0.5	0.25
Recharging time from 120 Vac	4.5 h	3.5 h	2.5 h	1.5 h
Recharging time from 12 Vdc	2.5 h	2 h	1.5 h	1 h


*Maximum charging time occurs when battery is completely discharged

Packaging Specifications

	Retail Package*	Inner Carton	Master Carton	Pallet
Size (L x W x H)	8.125 x 3.5 x 8" (20.5 x 8.6 x 20 cm)	18.25 x 8.875 x 9.75" (46.4 x 22.5 x 24.8 cm)	18.75 x 18 x 10.5" (47.6 x 45.7 x 26.7 cm)	40 x 48 x 77.5" (101.6 x 121.9 x 196.8 cm)
Count	1	5	10	280
Weight	2.1 lb (0.95 kg)	11.7 lb (5.3 kg)	25.9 lb (11.7 kg)	N/A
Volume	N/A	N/A	3,544 cu.in.	N/A
UPC number	715535890155			

* Blister Pack

Specifications subject to change without notice



Xantrex Technology Inc.

Headquarters
 8999 Nelson Way
 Burnaby, British Columbia
 Canada V5A 4B5

5916 195th Street NE
 Arlington, Washington
 USA 98223